



NOTES:

1. REFER TO STD DWG SL 12 FOR LOOP DETECTOR DETAILS.
2. MAINTAIN 12" MIN. SPACING BETWEEN SAW CUT, AND ANY CONCRETE JOINTS.
3. USE FLEXIBLE MATERIAL CROSSING JOINTS.
4. GRIND FLUSH WITH SURFACE AFTER CURED.

| REVISIONS |      |       |         |  |  |
|-----------|------|-------|---------|--|--|
|           |      |       |         |  |  |
|           |      |       |         |  |  |
|           |      |       |         |  |  |
|           |      |       |         |  |  |
|           |      |       |         |  |  |
|           |      |       |         |  |  |
|           |      |       |         |  |  |
|           |      |       |         |  |  |
|           |      |       |         |  |  |
|           |      |       |         |  |  |
|           |      |       |         |  |  |
| N.O.      | DATE | APPR. | REMARKS |  |  |

UTAH DEPARTMENT OF TRANSPORTATION  
STANDARD DRAWINGS FOR ROAD AND BRIDGE CONSTRUCTION  
SALT LAKE COUNTY

STANDARD DRAWINGS FOR ROAD AND BRIDGE CONSTRUCTION

~~SALT LAKE CITY, UTAH~~

RECOMMENDED FOR APPROVAL \_\_\_\_\_  
 CHAIRMAN STANDARDS COMMITTEE

*Donna R. Williams*  
 DATE JAN. 01, 2008

CHAIRMAN STANDARDS COMMITTEE

APPROVED

*[Signature]*

JAN.01,2008

DEPUTY DIRECTOR \_\_\_\_\_ DATE \_\_\_\_\_

DATE

JAN.01,2008

DATE \_\_\_\_\_

| NO. | DATE | APPR. | REMARKS |
|-----|------|-------|---------|
|-----|------|-------|---------|

## WEIGH IN MOTION PIEZO DETAILS

STANDARD DRAWING TITLE

STD DWG  
AT 14